

## Trinity EBC product code structure

### Castors

WHEEL				FORK					ELECTRONIC FEATURES					
Wheel product group	Tyre material	Bearing type	Wheel diameter	Fork product group	Pedal orientation	Colour way	Brake type	Fork design	Steering type	Cable type	Castor configuration	IPX rating		
<b>F</b> F Series	<b>U</b> Urethane 55 shore D	<b>Q</b> Precision bearing	<b>100</b> 100 mm	<b>P</b> Powered	<b>0</b> Inline	<b>E</b> Eggshell	<b>CB</b> Complete brake	<b>S</b> Standard	<b>I</b> Intuitive	<b>L</b> LINAk	<b>M</b> Motion sensing	<b>5</b> IPX5 rating		
	<b>A</b> Anti-static 55 shore D		<b>125</b> 100 mm		<b>9</b> 90 degrees	<b>C</b> Cool grey	<b>TB</b> Total brake	<b>A</b> Anti-static		<b>U</b> User specified		<b>D</b> DEWERT	<b>N</b> Non motion sensing	<b>6</b> IPX6 rating
			<b>150</b> 100 mm							<b>T</b> TiMOTION				

### Control System

<b>EBC Controller</b>	<b>EBCCONTROLI</b>	Intuitive
	<b>EBCCONTROLI</b>	User specified
<b>EBC Battery</b>	<b>EBCBATTERY1</b>	
<b>EBC Power supply</b>	<b>EBCPOWERAU</b>	Australian
	<b>EBCPOWEREU</b>	European
	<b>EBCPOWERUK</b>	United Kingdom
	<b>EBCPOWERUS</b>	United States
<b>EBC Handset</b>	<b>EBCHANDSETU5</b>	User-specified, 5 buttons
	<b>EBCHANDSETI1</b>	Intuitive, 1 button
	<b>EBCHANDSETI6</b>	Intuitive, 6 button
<b>EBC Control panel</b>	<b>EBCPANELI1</b>	
<b>EBC Castor control box</b>	<b>EBCINTERFACE</b>	
<b>EBC Y Cable</b>	<b>EBCCABLEY</b>	
<b>EBC Cable set</b>	<b>EBCCABLESET1.5</b>	Set of four 1.5 m

### Mounts

<b>SPWSHFZLASER</b>	Washer lasercut mount
<b>SPWSHFZDRILL</b>	Washer drill mount
<b>-AFR28Z(100125)</b>	Pintle for 100 mm & 125 mm wheels, 32 mm round stem
<b>-AFR28Z(150)</b>	Pintle for 150 mm wheel, 28 mm round stem
<b>-AFR32Z(100125)</b>	Pintle for 100 mm & 125 mm wheels, 32 mm round stem
<b>-AFR32Z(150)</b>	Pintle for 150 mm wheel, 32 mm round stem

### Trinity EBC Sets

Product	Wheel	Pedal	Colour	Brake	Steering	Cable	IPX rating
<b>EBCSET</b>	<b>100</b> 100 mm	<b>0</b> Inline	<b>E</b> Eggshell	<b>CB</b> Complete brake	<b>I</b> Intuitive	<b>L</b> LINAk	<b>5</b> IPX5 rating
	<b>125</b> 125 mm	<b>9</b> 90 degrees	<b>C</b> Cool grey	<b>TB</b> Total brake	<b>U</b> User-specified	<b>D</b> DEWERT	<b>6</b> IPX6 rating
	<b>150</b> 150 mm					<b>T</b> TiMOTION	

### For more information:

#### Fallshaw Wheels & Castors

2A Ayton Street, North Sunshine VIC 3020 Australia

Freecall: 1800 333 002 (within Australia) | International: +61 (03) 9300 8555

Email: sales@fallshaw.com.au

www.trinityebc.com.au