

Square knock-in tube ends

AF10/25/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded mild steel.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	44 mm
Load capacity	250 kg



\$ 4.20 (+ GST)

Square knock-in tube ends

AF10/25/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded mild steel.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	44 mm
Load capacity	250 kg



\$ 3.65 (+ GST)

Square knock-in tube ends

AF10/32/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded mild steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 7.20 (+ GST)

Square knock-in tube ends

AF10/32/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded mild steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 7.20 (+ GST)

Square knock-in tube ends

AF11/25/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	44 mm
Load capacity	250 kg



\$ 7.90 (+ GST)

Square knock-in tube ends

AF11/25/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M16
Knock-in length	39 mm
Overall length	44 mm
Load capacity	250 kg



\$ 9.95 (+ GST)

Square knock-in tube ends

AF11/30/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	30 mm
Internal tube size	26-27 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 9.55 (+ GST)

Square knock-in tube ends

AF11/30/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	30 mm
Internal tube size	26-27 mm
Thread diameter	M16
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 11.85 (+ GST)

Square knock-in tube ends

AF11/32/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 8.80 (+ GST)

Square knock-in tube ends

AF11/32/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 9.55 (+ GST)

Square knock-in tube ends

AF11/32/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M16
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 10.70 (+ GST)

Square knock-in tube ends

AF11/35/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	35 mm
Internal tube size	31-32 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	45 mm
Load capacity	400 kg



\$ 11.85 (+ GST)

Square knock-in tube ends

AF11/35/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	35 mm
Internal tube size	31-32 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	400 kg



\$ 13.05 (+ GST)

Square knock-in tube ends

AF11/38/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M10
Knock-in length	41 mm
Overall length	45 mm
Load capacity	500 kg



\$ 11.85 (+ GST)

Square knock-in tube ends

AF11/38/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M12
Knock-in length	41 mm
Overall length	45 mm
Load capacity	500 kg



\$ 11.85 (+ GST)

Square knock-in tube ends

AF11/38/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M16
Knock-in length	41 mm
Overall length	45 mm
Load capacity	500 kg



\$ 13.05 (+ GST)

Square knock-in tube ends

AF11/40/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 11.85 (+ GST)

Square knock-in tube ends

AF11/40/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 13.05 (+ GST)

Square knock-in tube ends

AF11/40/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M16
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$ 14.20 (+ GST)

Square knock-in tube ends

AF11/51/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	47 mm
Load capacity	750 kg



\$ 14.20 (+ GST)

Square knock-in tube ends

AF11/51/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	47 mm
Load capacity	750 kg



\$ 14.20 (+ GST)

Square knock-in tube ends

AF11/51/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M16
Knock-in length	39 mm
Overall length	47 mm
Load capacity	750 kg



\$ 16.55 (+ GST)

Ball-joint adjustable feet

AF20/40/M10/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M10
Thread length	60 mm
Base height	33 mm
Load capacity	500 kg



\$ 20.10 (+ GST)

Ball-joint adjustable feet

AF20/60/M12/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	60 mm
Pad height	20 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	800 kg



\$ 27.10 (+ GST)

Ball-joint adjustable feet

AF20/90/M20/100

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M20
Thread length	100 mm
Base height	51 mm
Load capacity	1,000 kg



\$50.70 (+ GST)

Ball-joint adjustable feet

AF21/40/M10/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M10
Thread length	60 mm
Base height	33 mm
Load capacity	500 kg



\$25.90 (+ GST)

Ball-joint adjustable feet

AF21/60/M12/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	20 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	800 kg



\$28.70 (+ GST)

Ball-joint adjustable feet

AF21/60/M16/165

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	25 mm
Thread diameter	M16
Thread length	165 mm
Base height	51 mm
Load capacity	1,000 kg



\$45.05 (+ GST)

Ball-joint adjustable feet

AF21/60/M16/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	25 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1,000 kg



\$35.75 (+ GST)

Ball-joint adjustable feet

AF21/90/M16/165

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	165 mm
Base height	51 mm
Load capacity	1,000 kg



\$48.60 (+ GST)

Ball-joint adjustable feet

AF21/90/M16/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1,000 kg



\$ 39.25 (+ GST)

Bolt-down adjustable feet

AF30/40/M10/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M10
Thread length	60 mm
Base height	33 mm
Load capacity	500 kg



\$ 20.55 (+ GST)

Bolt-down adjustable feet

AF30/60/M12/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	800 kg



\$ 30.35 (+ GST)

Bolt-down adjustable feet

AF31/40/M10/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M10
Thread length	60 mm
Base height	33 mm
Load capacity	500 kg



\$ 26.35 (+ GST)

Bolt-down adjustable feet

AF31/60/M12/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	800 kg



\$ 34.85 (+ GST)

Bolt-down adjustable feet

AF31/60/M16/165

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M16
Thread length	165 mm
Base height	51 mm
Load capacity	1,000 kg



\$ 48.60 (+ GST)

Bolt-down adjustable feet

AF31/60/M16/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1,000 kg



\$ 39.25 (+ GST)

Bolt-down adjustable feet

AF31/60/M20/100

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M20
Thread length	100 mm
Base height	51 mm
Load capacity	1,000 kg



\$ 97.00 (+ GST)

Bolt-down adjustable feet

AF31/90/M12/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	800 kg



\$ 34.85 (+ GST)

Bolt-down adjustable feet

AF31/90/M16/165

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	165 mm
Base height	51 mm
Load capacity	1,000 kg



\$ 48.60 (+ GST)

Bolt-down adjustable feet

AF31/90/M16/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1,000 kg



\$ 39.25 (+ GST)

Fixed adjustable feet

AF40/60/M12/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.
- Includes anti-slip vibration pad.

Pad diameter	60 mm
Pad height	20 mm
Thread diameter	M12
Thread length	60 mm
Load capacity	800 kg



\$ 15.35 (+ GST)

Fixed adjustable feet

AF41/40/M10/35

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.
- Includes anti-slip vibration pad.

Pad diameter	40 mm
--------------	-------

Pad height	20 mm
------------	-------

Thread diameter	M10
-----------------	-----

Thread length	35 mm
---------------	-------

Load capacity	500 kg
---------------	--------



\$12.10 (+ GST)

Fixed adjustable feet

AF41/40/M10/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.
- Includes anti-slip vibration pad.

Pad diameter	40 mm
--------------	-------

Pad height	20 mm
------------	-------

Thread diameter	M10
-----------------	-----

Thread length	60 mm
---------------	-------

Load capacity	500 kg
---------------	--------



\$7.50 (+ GST)

Fixed adjustable feet

AF41/60/M12/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and stainless steel.
- Includes anti-slip vibration pad.

Pad diameter	60 mm
--------------	-------

Pad height	20 mm
------------	-------

Thread diameter	M12
-----------------	-----

Thread length	60 mm
---------------	-------

Load capacity	800 kg
---------------	--------



\$17.70 (+ GST)

Round knock-in tube ends

AF81/25/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	25 mm
--------------------	-------

Internal tube size	22 mm
--------------------	-------

Thread diameter	M10
-----------------	-----

Knock-in length	38 mm
-----------------	-------

Overall length	46.5 mm
----------------	---------

Load capacity	100 kg
---------------	--------



\$8.50 (+ GST)

Round knock-in tube ends

AF81/25/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	25 mm
--------------------	-------

Internal tube size	22 mm
--------------------	-------

Thread diameter	M12
-----------------	-----

Knock-in length	38 mm
-----------------	-------

Overall length	46.5 mm
----------------	---------

Load capacity	100 kg
---------------	--------



\$9.70 (+ GST)

Round knock-in tube ends

AF81/32/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	32 mm
--------------------	-------

Internal tube size	28-29 mm
--------------------	----------

Thread diameter	M10
-----------------	-----

Knock-in length	39 mm
-----------------	-------

Overall length	45 mm
----------------	-------

Load capacity	250 kg
---------------	--------



\$8.50 (+ GST)

Round knock-in tube ends

AF81/32/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	250 kg



\$9.70 (+ GST)

Round knock-in tube ends

AF81/32/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M16
Knock-in length	32 mm
Overall length	45 mm
Load capacity	250 kg



\$10.90 (+ GST)

Round knock-in tube ends

AF81/38/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M10
Knock-in length	38 mm
Overall length	45 mm
Load capacity	300 kg



\$13.05 (+ GST)

Round knock-in tube ends

AF81/38/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M12
Knock-in length	38 mm
Overall length	45 mm
Load capacity	300 kg



\$13.05 (+ GST)

Round knock-in tube ends

AF81/40/M10

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M10
Knock-in length	39 mm
Overall length	45 mm
Load capacity	500 kg



\$13.05 (+ GST)

Round knock-in tube ends

AF81/51/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M16
Knock-in length	38 mm
Overall length	45 mm
Load capacity	450 kg



\$17.70 (+ GST)

Round knock-in tube ends

AF81/62/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	62 mm
Internal tube size	60-61 mm
Thread diameter	M16
Knock-in length	38 mm
Overall length	45 mm
Load capacity	450 kg



\$ 21.60 (+ GST)

Long threaded square tube ends

AFLTPS25/M10

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M10
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	250 kg



\$ 11.45 (+ GST)

Long threaded square tube ends

AFLTPS25/M12

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M12
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	250 kg



\$ 13.55 (+ GST)

Long threaded square tube ends

AFLTPS32/M10

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M10
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	350 kg



\$ 16.25 (+ GST)

Long threaded square tube ends

AFLTPS32/M12

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M12
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	350 kg



\$ 16.60 (+ GST)

Long threaded square tube ends

AFLTPS38/M10

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M10
Knock-in length	41 mm
Internal thread length	24 mm
Load capacity	500 kg



\$ 18.10 (+ GST)

Long threaded square tube ends

AFLTPS38/M12

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M12
Knock-in length	41 mm
Internal thread length	24 mm
Load capacity	500 kg



\$ 18.10 (+ GST)

Long threaded square tube ends

AFLTPS38/M16

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M16
Knock-in length	42 mm
Internal thread length	31 mm
Load capacity	500 kg



\$ 23.60 (+ GST)

Long threaded square tube ends

AFLTPS51/M10

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M10
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	750 kg



\$ 19.60 (+ GST)

Long threaded square tube ends

AFLTPS51/M12

- For use with castors.
- Stainless steel nut with a plastic thread behind it.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M12
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	750 kg



\$ 19.60 (+ GST)

Long threaded round tube ends

AFLTR25/M10

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M10
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	100 kg



\$ 16.60 (+ GST)

Long threaded round tube ends

AFLTR25/M12

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M12
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	100 kg



\$ 16.60 (+ GST)

Long threaded round tube ends

AFLTR32/M10

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M10
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	250 kg



\$ 16.95 (+ GST)

Long threaded round tube ends

AFLTR32/M12

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	32 mm
Internal tube size	28-29 mm
Thread diameter	M12
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	250 kg



\$ 17.40 (+ GST)

Long threaded round tube ends

AFLTR38/M10

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M10
Knock-in length	41 mm
Internal thread length	24 mm
Load capacity	300 kg



\$ 19.90 (+ GST)

Long threaded round tube ends

AFLTR38/M12

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M12
Knock-in length	41 mm
Internal thread length	24 mm
Load capacity	300 kg



\$ 19.90 (+ GST)

Long threaded round tube ends

AFLTR51/M12

Made from nylon with internal zinc plated mild steel thread. For use with castors.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M12
Knock-in length	42 mm
Internal thread length	31 mm
Load capacity	450 kg



\$ 21.55 (+ GST)

Long threaded square tube ends

AFLTS19/M10

- Suitable for use with castors.
- Made from nylon with zinc-plated mild steel thread.

External tube size	19 mm
Internal tube size	15-16 mm
Thread diameter	M10
Knock-in length	22.5 mm
Internal thread length	24 mm
Load capacity	50 kg



\$ 12.55 (+ GST)

Long threaded square tube ends

AFLTS40/M10

- Suitable for use with castors.
- Made from nylon with zinc-plated mild steel thread.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M10
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	500 kg



\$ 19.90 (+ GST)

Long threaded square tube ends

AFLTS40/M12

- Suitable for use with castors.
- Made from nylon with zinc-plated mild steel thread.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M12
Knock-in length	39 mm
Internal thread length	24 mm
Load capacity	500 kg



\$ 19.90 (+ GST)

Long threaded square tube ends

AFLTS51/M16

- Suitable for use with castors.
- Made from nylon with zinc-plated mild steel thread.

External tube size	51 mm
Internal tube size	47-48 mm
Thread diameter	M16
Knock-in length	39 mm
Internal thread length	31 mm
Load capacity	750 kg



\$ 24.00 (+ GST)

Ball-joint adjustable feet

AF20/40/M8/60

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M8
Thread length	60 mm
Base height	60 mm
Load capacity	350 kg



\$ 16.70 (+ GST)

Fixed adjustable feet

AF40/40/M8/35

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.
- Includes anti-slip vibration pad.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M8
Thread length	35 mm
Load capacity	350 kg



\$ 6.85 (+ GST)

Ball-joint adjustable feet

AF20/90/M16/65

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	60 mm
Base height	65 mm
Load capacity	1000 kg



\$ 32.20 (+ GST)

Ball-joint feet

AF21/90/M12/65

- Made from glass-reinforced nylon and stainless steel.
- Ideal for tables, machinery and equipment.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$ 34.85 (+ GST)

Ball-joint feet

AF21/90/M20/100

- Made from glass-reinforced nylon and stainless steel.
- Ideal for tables, machinery and equipment.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M20
Thread length	100 mm
Base height	51 mm
Load capacity	1000 kg



\$ 97.00 (+ GST)

Bolt-down ball joint feet

AF30/40/M8/60

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M8
Thread length	60 mm
Base height	33 mm
Load capacity	350 kg



\$ 17.55 (+ GST)

Bolt-down ball joint feet

AF30/60/M16/65

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$ 32.20 (+ GST)

Bolt-down ball joint feet

AF30/60/M16/150

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	60 mm
Pad height	23 mm
Thread diameter	M16
Thread length	150 mm
Base height	51 mm
Load capacity	1000 kg



\$ 39.25 (+ GST)

Bolt-down ball joint feet

AF30/90/M12/65

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$ 28.70 (+ GST)

Bolt-down ball joint feet

AF30/90/M16/65

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$ 32.20 (+ GST)

Bolt-down ball joint feet

AF30/90/M16/150

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	150 mm
Base height	51 mm
Load capacity	1000 kg



\$ 38.65 (+ GST)

CFR A-Justa-Foot

CFR41/22/M8/38

Anti-slip and anti-vibration feet suitable for domestic, commercial and light industrial applications.

Base material	Synthetic Rubber Shore 73
Pad diameter	22 mm
Overall height	48 mm
Thread diameter	M8
Thread length	38 mm
Base height	10 mm



\$ 6.00 (+ GST)

CFR A-Justa-Foot

CFR41/40/M8/48

Anti-slip and anti-vibration feet suitable for domestic, commercial and light industrial applications.

Base material	Synthetic Rubber Shore 73
Pad diameter	40 mm
Overall height	58 mm
Thread diameter	M8
Thread length	48 mm
Base height	10 mm



\$ 6.00 (+ GST)

CFP A-Justa-Foot

CFP41/40/M12/55

Anti-slip and anti-vibration feet suitable for domestic, commercial and light industrial applications.

Pad diameter	40 mm
Overall height	82 mm
Thread diameter	M12
Thread length	55 mm
Base height	25 mm
Load capacity	1000 kg



\$ 9.00 (+ GST)

Fixed adjustable feet

AF40/40/M10/35

- Ideal for tables, machinery and equipment.
- Made from glass-reinforced nylon and mild steel.
- Includes anti-slip vibration pad.

Pad diameter	40 mm
Thread diameter	M10
Thread length	35 mm
Base height	20 mm
Load capacity	500 kg



\$ 7.35 (+ GST)

Fixed adjustable feet

AF40/40/M10/95

- Made from glass-reinforced nylon and mild steel.
- Includes anti-slip vibration pad.

Pad diameter	40 mm
Thread diameter	M10
Thread length	95 mm



\$5.44 (+ GST)

Square knock-in tube ends

AF11/25/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	44 mm
Load capacity	250 kg



\$8.85 (+ GST)

Ball-joint feet

AF20/90/M12/65

- Made from glass-reinforced nylon and mild steel.
- Ideal for tables, machinery and equipment.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$30.35 (+ GST)

Bolt-down ball joint feet

AF30/90/M12/65

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M12
Thread length	65 mm
Base height	51 mm
Load capacity	800 kg



\$28.70 (+ GST)

Bolt-down ball joint feet

AF30/90/M16/65

- Made from glass-reinforced nylon and mild steel.
- Can be fixed to the floor to provide stability.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$32.20 (+ GST)

Ball-joint feet

AF20/90/M16/150

- Made from glass-reinforced nylon and mild steel.
- Ideal for tables, machinery and equipment.

Pad diameter	90 mm
Pad height	25 mm
Thread diameter	M16
Thread length	150 mm
Base height	51 mm
Load capacity	1000 kg



\$40.40 (+ GST)

Square knock-in tube ends

AF10/25/M16

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded mild steel.

External tube size	25 mm
Internal tube size	22-23 mm
Thread diameter	M16
Knock-in length	39 mm
Overall length	44 mm
Load capacity	250 kg



\$7.30 (+ GST)

Square knock-in tube ends

AF10/30/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded mild steel.

External tube size	30 mm
Internal tube size	26-27 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	350 kg



\$7.20 (+ GST)

Square knock-in tube ends

AF11/38/M8

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	38 mm
Internal tube size	35-36 mm
Thread diameter	M8
Knock-in length	41 mm
Overall length	45 mm
Load capacity	500 kg



\$11.85 (+ GST)

Ball-joint feet

AF20/60/M16/150

- Made from glass-reinforced nylon and mild steel.
- Ideal for tables, machinery and equipment.

Pad diameter	60 mm
Pad height	25 mm
Thread diameter	M16
Thread length	150 mm
Base height	51 mm
Load capacity	1000 kg



\$36.90 (+ GST)

Ball-joint feet

AF21/60/M12/165

- Made from glass-reinforced nylon and stainless steel.
- Ideal for tables, machinery and equipment.

Pad diameter	60 mm
Thread diameter	M12
Thread length	165 mm



\$24.98 (+ GST)

Ball-joint feet

AF20/60/M16/65

- Made from glass-reinforced nylon and mild steel.
- Ideal for tables, machinery and equipment.

Pad diameter	60 mm
Pad height	25 mm
Thread diameter	M16
Thread length	65 mm
Base height	51 mm
Load capacity	1000 kg



\$25.90 (+ GST)

Fixed adjustable feet

AF41/40/M8/35

- Made from glass-reinforced nylon and stainless steel.
- Includes anti-slip vibration pad.

Pad diameter	40 mm
Pad height	20 mm
Thread diameter	M8
Thread length	35 mm
Load capacity	350 kg



\$ 10.85 (+ GST)

Round knock-in tube ends

AF81/40/M12

- Suitable for adjustable feet (not castors).
- Made from nylon with threaded stainless steel.

External tube size	40 mm
Internal tube size	36-37 mm
Thread diameter	M12
Knock-in length	39 mm
Overall length	45 mm
Load capacity	500 kg



\$ 13.50 (+ GST)

Ball-joint feet

AF20/90/M12/150

- Made from glass-reinforced nylon and mild steel.
- Ideal for tables, machinery and equipment.

Pad diameter	90 mm
Thread diameter	M12
Thread length	150 mm



\$ TBA (+ GST)

